

# 2023 NEW ADDITIONS





#### 3 NEW DUAL ROW CONSUMER UNIT MODELS FURTHER EXTEND THE POPULAR LEWDEN PRO RANGE, NOW PERMITTING UP TO 39 USEABLE WAYS.

- > Equipped with 100A DP main switch and type 2 surge protection as standard.
- > Designed for use with Lewden RCBOs and AFDD RCBOs.
- > Supplied with comb busbars and all interconnecting cables.
- > The enclosure is fully open between rows, providing significant cabling space.
- > A selection of round cable entry knockouts on top and bottom faces.
- Large rectangular rear knockouts in four positions are designed for use with Lewden cable grommets.
- > Retained front cover screws help to prevent loss during installation.
- > A neutral and earth bar above each row allows tidy and rationalised wiring of neutral and earth conductors.

# **Dual Row Consumer Unit**

| Part number | Total Useable ways | Useable ways Top row | Useable ways Bottom row | Dimensions HxWxD mm |
|-------------|--------------------|----------------------|-------------------------|---------------------|
| PRO-RD21MS  | 21                 | 11                   | 10                      | 540 x 281 x 108mm   |
| PRO-RD29MS  | 29                 | 15                   | 14                      | 540 x 353 x 108mm   |
| PRO-RD39MS  | 39                 | 20                   | 19                      | 540 x 442 x 108mm   |



# Garage Distribution

- 4 module IP55 Weatherproof ABS Enclosure with transparent door
- Neutral and Earth bar
- Dimensions 226h x 118w x 102d mm

| Part Number  | Incomer                    | Outgoings                       |  |
|--------------|----------------------------|---------------------------------|--|
| E-GARAGE-63A | 63A 2P 30mA<br>Type A RCCB | 1xB6A MCB 6kA<br>1XB16A MCB 6kA |  |



### **MCBs**

The G06 MCB series has been further extended to include 4 new models

- 6kA short circuit breaking capacity
- Fully interchangeable with all Lewden 6kA MCBs, RCBOs, AFDD RCBOs

| Part Number | Rated Current | Trip Curve |
|-------------|---------------|------------|
| G06-1B25    | 25            | В          |
| G06-1C25    | 25            | С          |
| G06-1B63    | 63            | В          |
| G06-1C63    | 63            | С          |



#### **Compact RCBOs**

The Lewden compact RCBO series now includes 25A ratings in both switched and un-switched Neutral models

6kA short circuit capacity

• 30mA type A

| Part Number      | Rated Current             | Trip Curve |
|------------------|---------------------------|------------|
| RCBO-B25/30/SPA  | 25A 1P (Solid Neutral)    | В          |
| RCBO-C25/30/SPA  | 25A 1P (Solid Neutral)    | С          |
| RCBO-B25/30/1PNA | 25A 1P (Switched Neutral) | В          |
| RCBO-C25/30/1PNA | 25A 1P (Switched Neutral) | С          |



## **DIN Rail Terminal**

Compatible with all Lewden Consumer unit circuit protection devices (Main switch, 6kA MCBs, RCBOs, & AFDD RCBOs)

| Part number | Rated Current | Voltage | Poles |
|-------------|---------------|---------|-------|
| DRT1001     | 100A          | 230VAC  | 1     |



LEWDEN LTD Unit 4, Bradbury Drive, Springwood Industrial Estate, Braintree Essex CM7 2SD

Tel.: +44 (0) 1376 336 200 sales@lewden.co.uk





For instant access to technical support through our team of expert engineers.