



Palazzoli
GROUP



SURGE PROTECTION ENCLOSURES FOR POWER DISTRIBUTION

IP65 STEEL ENCLOSURES INCORPORATING
THE LEWDEN RANGE OF TYPE 2 AND TYPE 1-2 SPDS

- > A range of fully fitted Surge Protection Enclosures utilising the Lewden WME Range of IP65 Steel Enclosures.
- > Pre-fitted with the Lewden range of Single or Three Phase Surge Protection Devices.
- > Suitable for use in TN-C-S/TN-S and TT Networks.
- > Complete with SPD Protection device and all internal cabling.
- > Designed to accommodate up to 50mm² loop in - loop out supply conductors.
- > 1.2mm Sheet Steel construction, powder coated to RAL7035.
- > Fully compliant with the requirements of BS7671.



Palazzoli
GROUP

SURGE PROTECTION ENCLOSURES FOR POWER DISTRIBUTION

Single Phase



Part Number	Description	SPD Type	Protection/ Isolation device	Enclosure dimensions (HxWxD) mm
WME-SPD1PT1	IP65 Steel Enclosure fitted with Single Phase Type 1-2 SPD (SRG1123)	1-2	63A gG Fuse	400 x 300 x 150



WME-SPD1PT2	IP65 Steel Enclosure fitted with Single Phase Type 2 SPD (SRG1V1G)	2	40A 2P MCB	400 x 300 x 150
-------------	--	---	------------	-----------------

Three Phase



Part Number	Description	SPD Type	Protection/ Isolation device	Enclosure dimensions (HxWxD) mm
WME-SPD3PT1	IP65 Steel Enclosure fitted with Three Phase Type 1-2 SPD (SRG3123)	1-2	63A gG Fuse	400 x 400 x 200



WME-SPD3PT2	IP65 Steel Enclosure fitted with Three Phase Type 2 SPD (SRG3V1G)	2	40A 3P MCB	400 x 300 x 150
-------------	---	---	------------	-----------------

For additional information on our Surge Protection Devices please scan the QR code.



Palazzoli
GROUP

LEWDEN LTD
Unit 4, Bradbury Drive,
Springwood Industrial Estate,
Braintree
Essex
CM7 2SD

Tel.: +44 (0) 1376 336 200
sales@lewden.co.uk

www.lewden.com



For instant access to technical support through our team of expert engineers.