



- > Available in 2 sizes & 2 shapes (Round/Oval).
- > IP66 suitable for both indoor & outdoor applications.
- > IK10 high impact and anti vandal resistance making it perfect for student accomodation, social housing, high traffic circulation areas and building surrounds.













ROSS 280



Power (W)	Power Supply	Colour	Part Numbers
10W	Electronic	White	LL124000NLW
		Black	LL124001NLW
	Emergency	White	LL124025NLW
		Black	LL124026NLW

ROSS 330



Power (W)	Power Supply	Colour	Part Numbers
	Electronic	White	LL124010NLW
20W		Black	LL124011NLW
ZUVV	Emergency	White	LL124020NLW
		Black	LL124021NLW



corrosion c4 as for Per ISO9223



IP66Dust and water jets/immersion



IK10 High impact resistance



ENERGY SAVING

CLASSIFICATION


Insulation Class I (II on request)


LED 4000K CRI>80

CONSTRUCTION

Body: Polycarbonate

Diffuser: Polycarbonate/Polyglass







Available colours





LEWDEN LTD
Unit 4, Bradbury Drive,
Springwood Industrial Estate,
Braintree
Essex
CM7 2SD

Tel.: +44 (0) 1376 336 200 sales@lewden.co.uk

lewden.com/lux







